

## TEMADUR ELASTIC EXTRA

<b>DESCRIPTION</b>	A two component additive for polyurethane paints to improve the elasticity of the coat.		
<b>PRODUCT FEATURES AND RECOMMENDED USES</b>	<ul style="list-style-type: none"><li>◆ Used in TEMADUR paints and varnishes in order to improve the elasticity and impact strength of the coat.</li><li>◆ Recommended when flexible or brittle plastic materials are coated.</li><li>◆ Does not harm the weathering resistance of coating.</li></ul>		
<b>TECHNICAL DATA</b>			
<b>Specific gravity</b>	1.05 kg / l (mixed)		
<b>Product codes and mixing ratio</b>	Base	5 parts by volume	990 1264
	Hardener	1 part by volume	008 7590
<b>Recommended amount to be added</b>	30 % by volume of a mixture of TEMADUR ELASTIC EXTRA and hardener to be added to the TEMADUR mixture.		
<b>Directions for use</b>	Add the hardener separately to TEMADUR ELASTIC EXTRA and TEMADUR. Unite the mixtures and mix thoroughly, if necessary thin with thinner 1048.  <b>N.B.!</b> Do not use TEMADUR ELASTIC EXTRA alone.		
<b>Colours</b>	TEMADUR ELASTIC EXTRA is colourless. It can be used untinted or tinted to shades according to TEMADUR TCL base paint. If not tinted TEMADUR ELASTIC EXTRA may impair the hiding power of the paint.		
<b>VOC</b>	The Volatile Organic Compounds amount is 450 g/litre of paint.		
<b>HEALTH AND SAFETY</b>	Containers are provided with safety labels, which should be observed. Further information about hazardous influences and protection are detailed in individual health and safety data sheets. A health and safety data sheet is available on request from Tikkurila Oy.  For professional use only.		

The above information, based on laboratory tests and practical experience, has been proved valid at the date marked on the product data sheet. When necessary verify the validity of the product data sheet. The quality of the product is ensured by our operational system, based on the requirements of the standards ISO 9001 and ISO 14001. As a manufacturer we cannot be responsible for any damages caused by using the product against our instructions or for inappropriate purposes.

mko160206/snl311207/990 7590, 008 7590