

## TEMALAC ACCELERATOR

<b>DESCRIPTION</b>	An accelerator which makes the curing of TEMALAC FD 50 and FD 80 faster.
<b>PRODUCT FEATURES AND RECOMMENDED USES</b>	<ul style="list-style-type: none"><li>◆ Accelerates the curing of the paint film.</li><li>◆ Enables faster packaging of the painted objects.</li></ul>
<b>TECHNICAL DATA</b>	
<b>Volume solids</b>	15 ± 2 %. (ISO 3233)
<b>Weight solids</b>	21 ± 2 %.
<b>Specific gravity</b>	0.9 kg / l
<b>Product code</b>	900 0598
<b>Recommended usage</b>	Max. 5 - 10 % of the paint volume. Bigger amounts may reduce the gloss of the paint.
<b>Application</b>	Mix the paint. Add the required amount of accelerator. Thin with Thinner 1006, if necessary, and mix thoroughly.
<b>VOC</b>	The Volatile Organic Compounds amount is 715 g/litre of paint.
<b>HEALTH AND SAFETY</b>	Containers are provided with safety labels, which should be observed. Further information about hazardous influences and protection are detailed in individual health and safety data sheets. A health and safety data sheet is available on request from Tikkurila Coatings Oy.  For professional use only.

The above information, based on laboratory tests and practical experience, has been proved valid at the date marked on the product data sheet. When necessary verify the validity of the product data sheet. The quality of the product is ensured by our operational system, based on the requirements of the standards ISO 9001 and ISO 14001. As a manufacturer we cannot be responsible for any damages caused by using the product against our instructions or for inappropriate purposes.

mik020506/tmk170206/900 0598